# Trailer Axle Assembly





Ready to use Assembly for ease of fitment ● Long term economy ● Reliability of the genuine equipment for peace of mind ● Better tyre life ● Product superiority & durability for Longer life ● Safe and effective brake system ● Stringent quality control measures



### Technical Specification of Trailer ( Dummy ) Axle Assembly

| Tyre Outer to Outer         | 2399 mm              | Rated Axle Load              | 10200 Kg                |
|-----------------------------|----------------------|------------------------------|-------------------------|
| Spring Centre               | 1043 mm              | Weight of Axle               | 350 Kg                  |
| Wheel Track                 | 1816 mm              | Nominal Ground clearance     | 433 mm                  |
| Number of Wheel Bolts       | 10                   | Brake Drum Diameter          | 394 mm                  |
| Wheel Bolt size / PCD       | M22 X 2.5 on 335 PCD | Brakes Type 20 / 24          | Full Air Brakes (S-cam) |
| Section of Axle 14 mm thick | 135 mm X 150 mm      | Weight of grease in each hub | 500 gms                 |

Leyparts stands for the comprehensive range of genuine spares for Ashok Leyland vehicles and engines with 100% conformity to OE specifications.





# Trailer Axle Assembly

#### Major contents of Trailer Axle assembly

| S.No. | Description                          | Quantity |
|-------|--------------------------------------|----------|
| 1     | Dummy Rear axle                      | 1        |
| 2     | Hub-10 WB335mm PCD                   | 2        |
| 3     | Brake drum                           | 2        |
| 4     | Inner bearing 168.28x95.25x41.28mm   | 2        |
| 5     | Outer Bearing 139.99x82.55x36.51mm   | 2        |
| 6     | Wheel Bolt M22x2.5                   | 20       |
| 7     | Wheel Nut M22x2.5                    | 20       |
| 8     | Brake assembly LH 394x178            | 1        |
| 9     | Brake assembly RH 394x178            | 1        |
| 10    | Brake chamber Type20/24 (or) Type 20 | 2        |
| 11    | Slack Adjuster 160 pitch             | 2        |
| 12    | Axle tube Nut 3.125" thread dia      | 2        |
| 13    | Oil seal ring inner                  | 2        |
| 14    | Oil seal ring outer                  | 2        |
| 15    | Dist piece                           | 2        |
| 16    | Oil seal                             | 2        |
| 17    | Oil finger                           | 2        |

## Leyparts Trailer Axle

- Manufactured as per CMVR standards.
- Strong Axle tube.
- Superior material with higher tensile strength.
- Thicker and bigger box section to take higher load.
- Spring pads welded on top of housing for better strength.
- . Spring bottom clamp is superior material.
- Spindles are induction hardened for better strength and long life.
- Oil seal ring inner-outer, outer-outer dia induction hardened for better oil seal life.
- Friction welded design-world class design-higher.
  production rate and longer life-which is much better than butt welded design.
- Higher section modulus to take heavier loads.
- . Herculean hub and brake drums.
- . Superior quality bearings, axle nut and Oil seals.
- Commonality of parts with 3516 tractor rear axle.
- Excellent after-sales service of tractor and trailer in same workshop.

Always use Ashok Leyland Genuine Spares from





# Ashok Leyland

Spare Parts Division, 480, Anna Salai, Chennai-600 035 Phone: (044) 24341536, Fax: (044) 24340150 Website: www.ashokleyland.com www.leyparts.com

