The mini truck that carries more.....





- S-cam brakes
- Improved electrical system
- New-look cabin
- ▶ GVW 12900 Kgs
- ▶ Highest Loading span option 22 ft

Expect much more from the all-new ecomet 1212 Strong. This mini truck easily carries heavier payloads with high reliability at all times. It's rugged aggregates, which now include the new S-cam brake, improved clutch and reliable electricals, ensure low maintenance costs and high savings!







The ECOMET Advantage

- Powered by the fuel efficient 'H' Series engine.
- 120 HP with 392 Nm torque
- New responsive S-cam Brakes
- Improved, longer lasting clutch and fail-safe electricals
- Better drive line with 6 speed OD & 60SHO Drive head

Applications

- Market Load
- Construction
- Cement
- Steel

Anytime, Anywhere Service:

Nationwide coverage through strong network of :

- More than 200 Dealer outlets for Sales / Service / Parts support
- Above 150 Authorised Service Centers
- Ashok Leyland Trained Mechanics (approx 12000) Readily available spare parts - LEYPARTS
- Leyland Direct 24X7 National Helpline Service
- Mobile Service Vans

Options

- VISHVAS Annual Maintenance Contract
- Extended Service Package 2 years/2,00,000 kms
- Extended Warranty Package 3 years/3,00,000 kms The specifications are liable to change due to continuous improvements and are for reference only.

Your One - stop Solution

For vehicle Maintenance

Do not drill or weld on frame



Lower Maintenance Cost And Better Turnaround Time



Best Of Extended Warranty And Additional Service



Facine	IIIII and a Cultudar Turks Charged Intercepted			
Engine	"H" series 4 Cylinder Turbo Charged Intercooled			
Maximum Power	120 HP @ 2400 rpm			
Maximum Torque	392 Nm @ 1600 RPM			
Clutch	330 mm Dia Single Plate dry type-Hydraulic actuation			
Gear Box	Synchromesh 6S ODGB with FGR 8.28:1			
Max Speed in Top Gear	91.4 kmph			
Gradeability	25.6%			
Steering	Power Steering			
Frame	All steel ladder type with bolted construction			
Front Axle	Section Reverse Elliot			
Rear Axie	Fully Floating 60SH0 5.57:1 RAR			
Suspension	Shackle ended			
Cabin	All Steel factory built Tiltable Day Cabin			
Brakes	Full air - dual line S-cam Brakes			
Parking Brakes	Spring actuated, Pneumatic (on Rear only)			
Battery	12 V-100 AH			
Tyres	8.25x20-16 PR			


GVW	12900 Kgs				
Major Dimensio	ns (in m	m)			
Wheel base	2850	3970	4200	4750	
Front Overhang (Vehicle)	1338				
Rear Overhang (Vehicle)	1144	1780	2124	2470	
Overall Length (Vehicle)	5332	7088	7663	8558	
Overall Width(Cabin/Body)	2207/2280				
Front Track	1946				
Rear Track	1675				
Min. Ground Clearance	232				
Turning Circle dia	10700	16400	17000	18500	
Load Body Length	11.4Ft	17.2Ft	19Ft	22Ft	







24 x 7 National Helpline





Cab Chassis FSD/DSD **HSD**

